



# RubberLay

Standard Rubber Underlays

Acoustic rubber underlays **minimise noise transfer, echoes, impact** and **airborne noise** from travelling between floors, rooms and homes. These underlays can be used beneath soft and hard flooring, **perfect for households and commercial spaces.**

**THE FLOORING CONNECTION**

PTY (LTD)



# ACOUSTIC RUBBER UNDERLAY

Suitable for stretch fit, single-stick and double-stick installation methods.

2.5mm

For the installation of **solid wood and bamboo** (with glued and braced or double click system).

3.0mm

For installation of **all types of soft floor-coverings** such as needle punch, tufted, woven and natural fibre broadloom carpets and all types of carpet tiles.

5.0mm

For **plush installation of soft-floor coverings** needle-punch, tufted, woven and natural fibre broadloom carpets and carpet tiles.



**Excellent rebound**



Fully **recyclable**



Absorbs **noise** up to 40%



Increases floor covering **lifespan**



**Comfort underfoot**



Made from **recycled rubber**



**Prevents indentations** on floor coverings



**Saves Energy**



High **stability** and **durability**



**Produced locally**



**Under carpet heating**



**Anti-Allergenic**



**Anti-microbial**



Not air filled, **non-collapsing**



**Unaffected** by **moisture**



# SPECIFICATIONS

RubberLay 2.5mm	
Description:	Flat, thermo-acoustic 2.5 mm crumb-rubber underlay.
Rating:	Heavy residential and commercial use including castor wheels and wheeled vehicle traffic.
Use:	For the installation of solid wood and bamboo provided these are T&G (glued and braced) or have a double click system. A separate DPC has to be used (200 micron virgin PVC, overlapped and taped - placed on the screed with the ECO-LAY applied rubber-side down onto the DPC). For installation of all types of soft floorcoverings such as needlepunch, tufted, woven and natural fibre broadloom carpets and all types of carpet tiles. Suitable for stretch-fit, single-stick and double-stick installation methods.

RubberLay 3mm	
Description:	Flat, thermo-acoustic 3mm crumb-rubber underlay.
Rating:	Heavy residential and commercial use including castor wheels and wheeled vehicle traffic.
Use:	For the installation of solid wood and bamboo provided these are T&G (glued and braced) or have a double click system. A separate DPC has to be used (200 micron virgin PVC, overlapped and taped - placed on the screed with the ECO-LAY applied rubber-side down onto the DPC). For installation of all types of soft floorcoverings such as needlepunch, tufted, woven and natural fibre broadloom carpets and all types of carpet tiles. Suitable for stretch-fit, single-stick and double-stick installation methods.

RubberLay 5mm	
Description:	Flat, super thermo-acoustic 5mm crumb-rubber underlay.
Rating:	Heavy traffic commercial use including castor wheels and wheeled vehicle traffic.
Use:	Underlay for plush installation of all types of soft floorcoverings such as needle-punch, tufted, woven and natural fibre broadloom carpets, and all types of carpet tiles. Suitable for stretch-fit, single-stick and double-stick installation methods.

Get in touch

Website

Case Study



CLICK TO OPEN

[Jonathan@theflooringconnection.org](mailto:Jonathan@theflooringconnection.org)

+27 (0) 82 834 7377

[Sven@theflooringconnection.co.za](mailto:Sven@theflooringconnection.co.za)

+27 (0) 83 253 4283